

SG92R


SG92R

TowerPro 9g digital servo New version of SG90. POM with Carbon fiber gears set and control arms are more durable use than SG90 nylon gear and more torque. It is a good choice for park size 3D models , high speed jets and R/C airplane 250 450 RC helicopter

Specifications:

Weight: 9g Dimension: 23x12.2x27mm Stall torque: 2.5kg /cm(4.8v) Gear type: POM with carbon fiber Operating speed: 0.1sec /60degree (4.8v) Operating voltage: 4.8v Temperature range: $0^{\circ}C_{5}^{\circ}C_{5}^{\circ}C$ Dead band width:1us servo wire length: 25 cm Servo Plug: JR (Fits JR and Futaba) Servo arms & screws included and fit with Futaba servo arm. It's universal "S" type connector that fits most receivers, including Futaba, JR, Hitec ,GWS, Cirrus, Blue Bird, Blue Arrow, Corona, Berg, Spektrum. **CE & RoHS approved**

Product Description:



Product Configure Table:

Weight(g)	12
Torque(kg)(4.8v)	2.5
Speed(sec/60deg)	0.1
A(mm)	34.5
B(mm)	22.8
C(mm)	26.7
D(mm)	12.6
E(mm)	32.5
F(mm)	16