

Amano MSM Sprite

Multi-Space Meter



The Amano MSM Sprite terminal powered by Metric is a futureproof solution designed with the needs of smart cities in mind. This all-new parking terminal has been completely reimagined, combining enhanced functionality with a sleek design. The terminal offers greater security, enhanced power management, a rotatable solar panel and a customizable keypad.

The Sprite offers the latest EMV/PCI compliant payment options, Chip & Pin, Chip & Contactless and Contactless Only – which supports mobile contactless payment technology including Apple Pay®. The new terminal can also accept coins, bills, smart cards and coupons. The Sprite tariff engine supports real-time dynamic tariff configurations, allowing the operator to structure pricing based on demand and capacity.

Communicating with the Sprite terminal is simple with our user-friendly, back-office system allowing:

- Real-Time Transactions
- Remote Management
- Tariff Updates
- Time Synchronization
- Function Updates

Key Features


- Pay & Display Parking
- Pay-by-Space Parking
- Pay-by-Plate Parking
- Gated Parking
- LPR Integrated Payments
- Transit Ticketing Solutions
- HD Video Screen for added revenue opportunities
- Ultra Power Efficient

AMANO MSM
powered by **metric**


Amano MSM Sprite

Multi-Space Terminal

Mains



Solar



Manufactured by Metric Parking in an ISO 9001:2008 registered facility.
Specifications are approximate and are subject to change without notice.

SPECIFICATIONS

COMPLIANCE

PCI PA-DSS (Payment Application Data Security Standard) compliant

ELECTRICAL

Power Supply: 110v AC or 220/240v AC single phase
Street lighting supply, stand-alone battery operation and solar power with battery backup

Operating Voltage: 12v DC

Solar Power: Solar charged model supplied with 26 Ah battery

Hybrid Dual Power: Solar + AC Mains electricity

Battery Power: 26 Ah battery supplied for solar operation
26 Ah back-up battery supplied for AC operation

ENVIRONMENT

90%+ recyclable ROHS compliant, WEEE applicable, CE mark

Operating Temperature: -13°F to 140°F (-25°C to +60°C)

Humidity: Up to 95% (non-condensing)

HOUSING

Height: 59.09" (1501mm)

Width: 12.72" (318mm)

Depth: 12.20" (310mm)

Weight: Approximately 217 lbs. (98.4 kg)

Construction: Welded reinforced treated steel

Cabinet Finish: Standard color: Black. Optional colors: Green, Grey, Blue, Red and custom colors available

Display: 5.7" SD mono screen
5.7" SD color screen
7" HD color screen
8.4" HD color touch screen (mains only)

PAYMENT SYSTEMS

Coins, bills, chip & pin, credit/debit cards, tokens, contactless credit cards, contactless smart cards

Coin Acceptance: 15 channel coin validator, multi-currency capacity

Coin Box: 4,500 coin capacity (US quarters), self-locking, exchangeable

Bill Validator: Up to 16 currency values in 64 international banknotes

Cash Vault: 6 litre coin box/5 litre with banknote acceptor
Banknote Acceptor 600 or 1,000 capacity

TICKETS

Ticket Capacity: 4,000 ticket capacity, 5,500 with ECO paper

Ticket Printing: Thermal 8 dots/mm graphic printing

Ticket Size: Single ticket - 2.36"W x 2.36"L (60 mm x 60 mm)

SCANNER

Barcode scanner (coupons, event prepay)

SECURITY

Electronic locking

HEATER (Mains electrical only)

Standard - thermostatically controlled, optional vault area heater