CLEARVUE®

VIDEO LARYNGOSCOPE





CLEARVUETM

The Infinium ClearVue™ VL3R

Reusable Blade Video Laryngoscopes

The Infinium ClearVue[™] Video Laryngoscopes are:

COMPACT AND ERGONOMIC

- Lightweight Unit Is Less Than 350g.
- Quick installation and Removal of Blade
- Quick Shot Camera Button for Recording

LOW COST PER PATIENT

Reusable Blades Can Be Used Up to 1000 Times

DURABLE

- 2 Years Warranty
- Screen is Reinforced With Anti-Shatter Protection
- Light Weight Long Lasting Rechargeable Lion Battery

HIGH-DEFINITION

- 3.5 Inch Display
- Anti-Fog Lens
- 2.0 Mega Pixel Camera With Video
- Optional HDMI External Monitor





The ClearVue™ VL3R comes standard with size 2, 3, and 4 reusable Mac blades.









Options blade sizes available are: Miller 0, Miller 1, Mac, 1 and Mac 5.



CLEARVUETM



The Infinium ClearVue™ VL3D

Disposable Blade Video Laryngoscopes

The Infinium ClearVue® video laryngoscope adopts state-of-the-art image technology and possesses the advantage of a 2.0 megapixel fullview camera with high-resolution monitor. The ClearVue® features a rechargeable li-ion battery for extended use. A unique anti-fog capability is also provided. The overall design is compact and ergonomic. A high resolution view of the glottis will enable clinicians first-attempt success while minimizing any chance of a complication during the intubation process.

- Rigid steel chassis construction
- Blade sizes 1, 2, 3, 4, and 5 available
- Vacuum Packed blades
- Low Cost Disposable Blades
- 1 Year Warranty





Size 1, 2, 3, 4, and 5 disposable Mac blades are available for the ClearVue™ VL3D.

CLEARVUE® TECHNICAL SPECIFICATIONS:

DISPLAY

Size 3.5"Full View

Monitor LCD; Scratch-resistant and

anti-glare screen

Resolution Ratio 640*480 RGB

Aspect Ratio 4:3
Video Refresh Rate 30FPS
Illumination LED

LARYNGOSCOPE BLADE CAMERA INCLUDED

Resolution Ratio 2.0M Pixels

Field Angle 66° illuminance ≥800LUX

BATTERY

Type Rechargeable Lithium Battery

Long working time ≥120minutes

Voltage 3.7V Capacity 3200mAh

Charging times More than 300 times

Charging time 4 hours

POWER ADAPTER

Charging port Micro USB

Input 100-250V,50/60Hz

Output 5V/2A

TRANSPORT/ STORAGE

Temperature -10 ~+45

CONDITION

Humidity ≤93

AP 500hPa to 1060hPa

WORKING CONDITION

Temperature 5 ~+40 Humidity 30 ~85

AP 700hPa to 1060hpa

UNIQUE ANTI-FOG FUNCTION

Auto anti-fog function upon powering on

WEIGHT

321 g(disposable system); 376g (reusable system) - light-weight, portable, comfortable

PHOTO/VIDEO FUNCTION

One click image capture 4G internal memory card for video and images USB connection cable for uploading images and video

HANDLE

ABS material - Comfortable ergonomic short handle design

